



NEW FROM SOLAX

X3-FORTH



X3-FORTH

80kW/100kW/110kW
120kW/125kW/136kW/150kW



Features

More energy harvest

- Maximum efficiency up to 99%
- 180~1000Vdc MPPT voltage range
- Maximum 12 MPPTs, 2 strings per MPP tracker
- 150% PV oversizing input, 110% overloading output
- Maximum 32A MPPT current

Safety & Reliability

- IP66 protection level
- AFCI protection (Optional)
- AC terminal temperature detection
- Both AC&DC SPDs(Type II) inside, Type I+II SPD is optional

Intelligence for easy maintenance and economy

- Built-in export power control
- Remote setting and upgrading
- 24 hours operation monitoring
- Smart I-V Curve Diagnosis supported
- Night-time reactive power compensation
- Aluminium AC cable connection available
- Power line communication (PLC)(Optional)
- Fuse free design with smart string current monitoring
- Smart air cooling technique results in long lifetime of fans
- Advanced heat dissipation technology makes the system more than 5% lighter and smaller

Contact Us for More Information

info@solaxpower.com
service@solaxpower.com



www.solaxpower.com

AU: +61 1300 476529

DE: +49 6142 4091664

Global: +86 571-56260008

UK: +44 2476 586998

NL: +31 (0) 852 737932

X3-FORTH (THREE PHASE)

X3-FTH-80K X3-FTH-100K X3-FTH-110K X3-FTH-120K X3-FTH-125K X3-FTH-136K-MV X3-FTH-150K-MV

DC INPUT							
Max. PV array input power [kWp]	120	150	165	180	188	204	225
Max. PV input voltage [V]	1100	1100	1100	1100	1100	1100	1100
Startup voltage [V]	200	200	200	200	200	200	200
Nominal input voltage [V]	580/600	580/600	580/600	580/600	580/600	730/785	730/785
MPP tracker voltage range [V]	180~1000	180~1000	180~1000	180~1000	180~1000	180~1000	180~1000
No. of MPP trackers	9	9	9	12	12	12	12
Strings per MPP tracker				2			
Max. input current per MPPT [A]				32			
Max. short circuit current per MPPT [A]				46			
AC OUTPUT							
Nominal AC output power [kW]	80	100	110	120	125	136	150
Nominal AC output current [A]	121.3/116	151.6/145	166.7/159.5	181.9/174	189.4/181.2	157.1/145.4	173.2/160.4
Max. AC output apparent power [kVA]	88	110	121	132	132	149.6	165
Max. AC output current [A]	133.4/127.6	166.7/159.5	183.4/175.4	200/191.3	200/191.3	172.8/160	190.6/176.5
Nominal AC voltage[V]		220/380, 230/400, 3/N/PE, 3/PE				500/540,3P3W+PE	500/540,3P3W+PE
Nominal grid frequency [Hz]				50/60			
Displacement power factor				0.8 leading-0.8 lagging			
THDi (Rated power) [%]				<3			
SYSTEM DATA							
MPPT efficiency [%]				99.9			
Max. efficiency [%]	98.6	98.6	98.6	98.6	98.6	99.0	99.0
Ingress protection				IP66			
Operating temperature range [°C]				-30~+60 (Derating above 45)			
Max. operation altitude [m]				4000 (Derating above 3000)			
Relative humidity [%]				0~100			
Dimensions[WxHxD] [mm]				985x660x327.5			
Weight [kg]	83	83	83	87	87	87	87
Cooling concept				Smart fan cooling			
Communication interfaces				RS485 / (Optional: Pocket WiFi/LAN/4G) / PLC(Optional) / USB			
Display				LCD(Optional)/LED*4			
PROTECTION							
Over/under voltage protection				YES			
DC isolation protection				YES			
Grid monitoring				YES			
DC injection monitoring				YES			
Residual current detection				YES			
Anti-islanding protection				YES			
String fault detection				YES			
SPD (DC/AC)				Type II / Type II			
Arc-fault circuit interrupter(AFCI)				Optional			
AC terminals over temperature detection				YES			
AC auxiliary power supply(APS)				Optional			
Power line communication(PLC)				Optional			
STANDARD							
Safety				IEC/EN 62109-1; IEC/EN 62109-2; NB/T 32004			
EMC				IEC/EN 61000; NB/T 32004			
Certification				EN 50549; AS4777.2; VDE4105; IEC 61727; IEC 62116; IEC 61683; IEC 60068; EN 50530; NB/T 32004			