



MEPV 300 - 320W


Covered cell interconnections | 5 Busbar | 6 Diodes

Quality

- / IP67 + 1 m cable
- / High transmissivity glass and high resistance
- / Frame with higher mechanical strength and air chamber
- / Friendly environment & recyclable materials
- / Electroluminescence test

Certificates

- / IEC 61215:2005
- / IEC 61730-1:2004 / IEC 61730-2:2004
- / Frontal load (snow) 5.400 Pa
- / Back load (wind) 2.400 Pa
- / Fire Resistance Certificate
- / Class I (under standard UNI 9177)
- / EE016-20130528-001 (France)
- / WEEE compliance in Germany
- / ETL Listed Mark (USA-Canada)
- / VKF-AEAI compliance (Switzerland)
- / MCS (UK)



TOTAL 65
 + 20 YEARS WARRANTY
 + 20 YEARS EXPERIENCE
 + 25 YEARS PERFORMANCE

+3%

Extra power
 extra up to 3%
 extra up to 7W



EUROPEAN QUALITY

PHOTON Laboratory talks about our modules:

"Eurener is one of the oldest module manufacturers in Europe: the Spanish company was founded in 1997. [...] Is distinguished by having values that are over the average: the temperature coefficient is quite better than other modules that are in the test field. The curve behavior at different irradiance conditions shows a marked efficiency increase in radiations from medium to high, and a slight drop in efficiency at low irradiance conditions. These factors show that this module could reach higher performance than the average in long-term measurements".



TURBO SUPERIOR

Monocrystalline Standard - All Black / 300 / 305 / 315 / 320W



25 years performance warranty

20 years product warranty

eurener
 energía solar

Technical features

Frame
Black / Silver anodized aluminium 0,015 mm
Covered cell interconnections
Robust and resistant to corrosion
Built-in plug
Connection box
Sealed, robust and wide for heat dissipation
IP67 according to IEC 60529
Diodes by-pass built-in (6) for protection of the partial shading
Connector MC4 or compatible, easy and rapid connection
Cables 1 meter length and 4mm ² section
Reaction to Fire Class I (conformity to UNI 9177 norm)
Frontal
3,2 mm tempered glass
Textured, extra-clear with low iron content
Solar cells
60 cells monocrystalline silicon / 156x156 mm
Weight and dimensions (L x W) +/-1% mm
20 Kg 1640/50 x 992 x 35/40 mm



Electric data

Standard - All Black	MEPV 300	MEPV 305	MEPV 315	MEPV 320
Nominal power, P _{mpp}	300W	305W	315W	320W
Tolerance, P _{mpp}	0 / +3%	0 / +3%	0 / +3%	±1%
Area of the module	1,62			
Module efficiency	18,52%	18,83%	19,44%	19,75%
I _{sc}	9,89 A	9,91 A	9,95 A	9,98 A
U _{oc}	39,75 V	39,98 V	40,50 V	40,85 V
I _{mp}	9,37 A	9,52 A	9,82 A	9,97 A
U _{mp}	32,02 V	32,04 V	32,08 V	32,10 V
Maximum voltage	1000 V			
I _{sc}	0,05% / °C			
U _{oc}	- 0,29% / °C			
g P _{max}	- 0,39% / °C			
Temperature range	- 40°C to +85°C			
NOCT	44°C ± 2°C			

NOTE: Read the instruction manual of this product and follow the indications. Values are valid for: 1000W/m², AM 1,5 and cell's temperature of 25°C. All the information of this brochure may be amended without notice by Eurener.

Sales Office:
Av. Marqués de Sotelo, 1-4^a
46002 Valencia (Spain)

Tel. +34 96 004 55 15
contact@eurenerworld.com

Official Distributor:

NED
[NOUVELLES ENERGIES DISTRIBUTION]

